


1. Performance Specifications


RFID Chip	NXP U Code 7	
Protocol	ISO/IEC 18000-6C, EPCglobal Class 1 Gen 2	
Operating Frequency	860~960MHz	
Operating Mode	Passive(Battery free)	
Memory	48bit TID, 128 bit EPC,0bit User Memory	32Bits Access, 32Bits Kill
IC Life	100,000 Programming cycles, 10 years data retention	
Benefits	Average reading distance >6m (Reader and Environment Dependent)	

2. Mechanical Dimensions

NO.	Item	Parameter(mm)	Tolerance	Parameter(in.)
1	Antenna Width	95.00 mm	± 0.20 mm	3.740 in.
2	Antenna Length	8.00 mm	± 0.20 mm	0.315 in.
37	Label Width	98.20 mm	± 0.20 mm	3.866 in.
38-1	Label Length	11.31 mm	± 0.50 mm	0.445 in.
38-2	Label Length (Middle)	12.31 mm	± 0.50 mm	0.485 in.
42	Label Pitch	15.88 mm	± 1.00 mm	0.625 in.
43	Antenna Edge to Label Edge (Left)	1.58 mm	± 1.50 mm	0.062 in.
44	Antenna Edge to Label Edge (Right)	1.58 mm	± 1.50 mm	0.062 in.
45	Antenna Edge to Label Edge (Top)	1.60 mm	± 1.50 mm	0.063 in.
46	Antenna Edge to Label Edge (Bottom)	1.60 mm	± 1.50 mm	0.063 in.
47	Label Edge to Liner Edge (Top)	1.59 mm	± 1.50 mm	0.063 in.
48	Label Edge to Liner Edge (Bottom)	1.59 mm	± 1.50 mm	0.063 in.
53	Liner Width	110.36 mm	± 1.00 mm	4.345 in.
55	Ink-dot Size	4.00 mm	± 2.00 mm	0.157 in
58	Ink-dot to Product Edge(Right)	6.15 mm	± 2.00 mm	0.242 in
59	Ink-dot to Product Edge(Top)	49.40 mm	± 2.00 mm	1.945 in
60	Core inner diameter	154.20 mm	± 1.00 mm	6.071 in.
61	Reel Outer diameter	(Based on the actual shipment quantity)		
62	Label Corner Radius	1.59 mm	± 0.20 mm	0.063 in.



3. Label Structure



Surface Material	White art paper	80g/m ² ± 10%, 72μm ± 10%
Adhesive 1	Acrylic emulsion	19g/m ² ± 5g/m ²
Antenna	Aluminum etching	AL + PET (10μm + 50μm)
Adhesive 2	Acrylic emulsion	19g/m ² ± 5g/m ²
Release Paper	White glassine paper	61g/m ² ± 10%, 55μm ± 10%

4. Environment Requirement

Operating Temperature/Humidity	-0~60°C / 20%~80% RH	
Storage Temperature/Humidity	20~30°C / 20%~60% RH	
Shelf Life	1 year in anti-static bag at 20~30°C / 20% ~60% RH	
ESD Voltage Immunity	2 kV (HBM)	
Bending Diameter	> 50mm	

5. Delivery Details

Appearance	Single row reel form	
Quantity	5000 ± 100pcs/Roll; 4 Rolls/Carton	Based on the actual shipment quantity
Weight	To be determined	
Final inspection	100 %, known faulty ones marked	
Delivery yield	≥ 99%	



AllGood-Group reserves the right for modifying the specification data without notice in advance!